















Zona V


- 
-  0,5m
- IP68
- 350mA
- IK10
-  0,30m
- 
- 

 code: 8084V. XXX . 16








Zona H


- 
-  0,5m
- IP68
- 350mA
- IK10
-  0,30m
- 
- 

 code: 8084H. XXX . 16



Zona X

- 
-  0,5m
- IP68
- 350mA
- IK10
-  0,30m
- 
- 

 code: 8084X. XXX . 16  
led color

LED	
<b>D30</b>	3,2W - Daylight 5000K
<b>W30</b>	3,2W - Warm white 2700K

COLOR	
<b>16</b>	Brushed stainless steel 316L



**DESCRIPTION**

Body made in stainless steel 316L  
 max. 1500kg  
 Degree of protection IP68  
 Safety clear plexiglass  
 Led 3,2W - 350mA incorporated  
 Provided with 1m cable

**ACCESSORIES**

Recessed box - Pop 9  
 Led driver 350mA CC

**ON REQUEST**

RAL colors  
 Other materials (brass / aluminum / ... )  
 Other led colors : 3000K / 4000K  
 Other dimensions (customized)

efficacy  
 120lm/W  
 D30

Typical luminous flux (lm)	
3,2W	
2700 K	305
3000 K	325
4000 K	340
5000 K	385

