LEDS C4





05-9758-34-37 V0

MICENAS Effect Wall recessed

Description

Wall recessed for outdoor use.

For frontal lighting and downlighting. Includes flush-mounting box. Specially designed to conceal all mounting screws. Structure material: Injected aluminium. Structure finish: Grey. Diffuser material: Glass. Diffuser finish: Transparent. UV protection. Warranty: 5 Years.

Finish

Grey

Transparent

Material

Injected aluminium

Glass

TECHNICAL CHARACTERISTICS

Light source

Light source: LED CREE Output (W): 2.2W

Total power consumption (W): 3.7W

CRI: 80

Photobiological risk: RG2

Real Lumen: 70 Qty Leds: 1 Lm/Real W: 19

Life Time: 50.000h L70B30 Bin / Grup: 7C1 o 7B4 MacAdam steps: 3

UGR: 6.5

GEAR

Brand: HILITE Gear included: Yes, electronic Voltage / Frequency: 100-240 VAC

Color temperature: Warm White - 3000K Power Factor: 0.54

Luminaire

Double cable exit: No Drainage: No Uv Protection: Yes Warranty: 5 Years

Logistics

Energy Efficiency: LED A++ EAN Code: 8435381409012 Net Weight (Kg): 0.430 Weight in Kg (packaged): 0.500

Packing: 175 x 70 x 80

Masterbox: 18

The photograph may not match the reference exactly. Please read the product description to identify the finish.







