

55-9972-CA-CM

V0

Gea COB Led Uplight recessed



Description

Floor recessed for indoor and outdoor use.

For uplighting. Electronic components are in a sealed internal compartment, completely separate from the compartment where the connection terminals are located. The unit will withstand a static weight of 1,800 Kg and the occasional transit of slow-moving vehicles. Includes 2 anti-glare accessories. Includes 2 reflectors. Includes flush-mounting box. Suitable for installation in marine environments. Includes 2 cable outlets to facilitate chain mounting. Adjustable light source. Structure material: Stainless steel AISI316, High purity aluminium. Structure finish: Polished, Black. Diffuser material: Glass. Diffuser finish: Tempered. UV protection. Warranty: 5 Years.

Finish

Polished  
Black  
Tempered

Material

Stainless steel AISI316  
High purity aluminium  
Glass

IP65/IP67 IK10 24° ±15° 360° 1

TECHNICAL CHARACTERISTICS

Light source

Light source: LED CREE  
Output (W): 34.7W  
Total power consumption (W): 35 W  
Color temperature: Neutral white - 4000K  
CRI: 80  
Photobiological risk: RG1  
Real Lumen: 3927  
Qty Leds: 1  
Lm/Real W: 112  
Life Time: 50.000h L90B10  
Bin / Grup: 40H  
MacAdam steps: 2  
UGR: 14.2

GEAR

Brand: MEANWELL  
Gear included: Yes, electronic  
Voltage / Frequency: 90-305 VAC  
Power Factor: 0.95  
Dimming protocol: 1-10V  
Flickering: 2.2%

Luminaire

Double cable exit: Yes  
Drainage: Yes  
Recessed: Si  
Public Areas: 1500  
Seaside: Yes  
Uv Protection: Yes  
Warranty: 5 Years

Logistics

Energy Efficiency: LED A++  
EAN Code: 8435381499242  
Net Weight (Kg): 5.965  
Weight in Kg (packaged): 6.817  
Packing: - x - x -  
Masterbox: 1

The photograph may not match the reference exactly. Please read the product description to identify the finish.



