



Simple Arc LED



Luminaire for universal use in all types of office spaces: hallways, conference rooms, computer rooms etc. Simple ARC LED is available with OPAL diffuser. The possibility of DALI lighting control - on request.

Materials: powder painted steel sheet body (standard color: white), OPAL diffuser made of polycarbonate

Installation: into modular ceilings 600x600 with a visible supporting structure. The luminaire should be installed together with original ceiling panels which are not part of the order

Power: 230 V

ELECTRICAL DATA

Light source	LED
Luminaire power	14 W
Number of light sources	1
Light source power	11W
Type of equipment	AC
Voltage rating	220 ... 240 V
Light source included	Yes
Type of LED	5630

MECHANICAL DATA

Type of installation	For 600x600 ceiling
Housing material	Steel sheet
Designed for light-line	No

INFORMATION

Colour	White
--------	-------

CERTIFICATES

Degree of protection (IP)	IP20
Degree of protection (IP) / top/	IP20
Class of protection	I
Energy class	A+
CE	Yes
CNBOP	No

LIGHT DATA

Luminaire's luminous efficiency	71 %
Light colour	White
Color rendering index	80
Light distribution	Mid beam
Light distribution	DI
Class of luminaire	I
Light output degradation	B10
Lumen maintenance	L90
Lifetime	> 54000 h
MacAdam	SDCM 3
Lamp Lumen Maintenance Factor (after 60 000h)	89 %

OPTICAL DATA

Louver/ shutter	OPAL
Diffuser colour	White
Diffuser material	Opal plastic

AVAILABLE VARIANTS

Product code	Luminaire luminous flux [lm]	Luminaire's luminous efficacy [lm/W]	Colour temperature
PX2067051	1220	87	3000K
PX2067052	1260	90	4000K

